

A Donaldson Company

A WORLD LEADER IN FUME EXTRACTION TECHNOLOGY



AD Base 3

Last Updated on 08.04.202

The laser companion advantage extraction system for the laser engraving industries.

The Advantage Base 3 has been designed specifically for the universal Versa laser engraver. The dimensions of the unit allow the Versa laser to fit perfectly onto the extractor, effectively doubling it up as a workstation.

The unit is also offered with an onboard air compressor to provide the laser with its air assist requirements and comes complete with an extraction hose kit and compressor link up on compressor models.

DeepPleat DUO pre-filter



HEPA filter



(RFA) technology



Advanced carbon filter (ACF) technology



Patented technology



ProTECT service plan



Technology

SureCHECK quality standard

Key features of the AD Base 3

Filter condition indicator Standard

DeepPleat DUO pre-filter Standard

On-board compressor Optional

Filter change / system fail signal Optional Low noise level Standard

VOC gas sensor (Volatile Organic Compound) Optional

Remote stop / start interface Optional

Contact BOFA at https://bofainternational.com/en/contact/

https://bofainternational.com/en/portal/datasheets/ad-base-3/



Approvals: REACH and RoHS. See individual product technical data for specific accreditations

Technical specification



Airflow through filters



Technical data

	EU	US
Dimensions (HxWxD)	775 x 510 x 680mm	30.51 x 20.08 x 26.77
Cabinet construction	Powder coated mild steel	Powder coated mild steel
Airflow / pressure	180m³/hr / 30mbar	105cfm / 30mbar
Electrical data	230v Single-phase 1~ 50/60Hz Full load current: 0.9 amps / 0.35kw	115v 60/50Hz Full load current: 1.2 amps / 0.35kw
Noise level	< 56dBA (at typical operating speed)	< 56dBA (at typical operating speed)
Weight	74kgs	163lbs
Approvals	UKCA and CE	UKCA and CE

DeepPleat DUO pre-filter specifications		
Surface media area	12m² approx (129.12ft²)	
Filter media	Borosilicate	
Filter media construction	Pleated with glue bead spacers	
Filter housing	Mild steel	
Filter efficiency	95% @ 0.9 microns	

Combined filter specifications	
HEPA filter media	Borosilicate
HEPA media construction	Maxi pleat
Surface media area	2.75m² approx (29.59ft²)
Filter housing	Mild Steel
Treated activated carbon	9kgs (19.8 lbs)
Filter efficiency	99.997% @ 0.3 microns

Part numbers						
Model	Voltage	Part no.	24V stop / start	Filter change / system failure signal	VOC monitoring	Compressor
AD Base 3 powder coated	230V	L0342A	A2001	A2002	A2003	A2007
	115V	L0341A	A2001	A2002	A2003	A2007

Replacement filters		
Model	DeepPleat DUO pre-filter	Combined filter
AD Base 3	A1030045	A1030050

Hose kit	
75-75mm kit	
Part no. A1020017	
1.5m 75mm flexible hose	
2 x connection cuffs	
75mm - 75mm Kit	

Other languages

Where applicable, the carbon used in BOFA units is capable of removing a wide range of VOCs, however it is the responsibility of the user to ensure the carbon is suitable for their application. For specific applications, please contact us for details.

Important Notice: Many factors beyond the control of BOFA can affect the use and performance of BOFA products in a particular application, including the conditions under which the product is used. Since these factors are uniquely within the user's knowledge and control, it is essential the user evaluate the products to determine whether the product is fit for the particular purpose and suitable for the user's application. All products, product specifications, availability and data are subject to change without notice, and may vary by region or country.

Think before you print! Please consider the environment before printing this document.

